

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 19.03.2015

Version number 3

Revision: 19.03.2015

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1 Product identifier**

**Trade name:** Osmo Polyx®-Oil 2K Pure, component A

**Article number:** 6125/A

**1.2 Relevant identified uses of the substance or mixture and uses advised against**

**advised against** No further relevant information available.

**Application of the substance / the mixture**

Coating compound/ Surface coating/ paint  
Paint

**1.3 Details of the supplier of the safety data sheet**

**Manufacturer/Supplier:** Osmo Holz und Color GmbH & Co. KG  
Affhüppen Esch 12  
D-48231 Warendorf

**Further information obtainable from:**

Product safety department  
Phone: +49 (0) 251 / 692 - 188  
Fax: +49 (0) 251 / 692 - 462  
e-mail: helmut.starp@osmo.de

**1.4 Emergency telephone number:**

emergency phone no. Berlin (24h): +49 (0) 30 / 30686 790 advisory service in German and English

**SECTION 2: Hazards identification**

**2.1 Classification of the substance or mixture**

**Classification according to**

**Regulation (EC) No 1272/2008** The product is not classified according to the CLP regulation.

**Classification according to**

**Directive 67/548/EEC or Directive**

**1999/45/EC** Not applicable.

**Information concerning**

**particular hazards for human and environment:**

The product does not have to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

**Classification system:**

The classification is according to the latest editions of the EU-lists and extended by company and literature data.

**2.2 Label elements**

**Labelling according to Regulation**

**(EC) No 1272/2008** Void

**Hazard pictograms** Void

**Signal word** Void

**Hazard statements** Void

(Contd. on page 2)

**Safety data sheet**  
 according to 1907/2006/EC, Article 31

Printing date 19.03.2015

Version number 3

Revision: 19.03.2015

**Trade name: Osmo Polyx®-Oil 2K Pure, component A**

(Contd. of page 1)

<b>Precautionary statements</b>	Although this product is not subject to identification regulations, we recommend that the safety suggestions are observed. Keep out of reach of children.
<b>Additional information:</b>	If medical advice is needed, have product container or label at hand. Observe the general safety regulations when handling chemicals. Always wear a dust mask when sanding. Contains 2-butanonoxime. May produce an allergic reaction.
<b>Information concerning particular hazards for human and environment:</b>	Warning: Wash out any used cloth impregnated with this product immediately after use or store in an airtight container (danger of self-ignition)
<b>2.3 Other hazards</b>	
<b>Results of PBT and vPvB assessment</b>	
<b>PBT:</b>	Not applicable.
<b>vPvB:</b>	Not applicable.

**SECTION 3: Composition/information on ingredients**
**3.2 Mixtures**

<b>Description:</b>	Mixture of substances listed below with nonhazardous additions.
<b>Dangerous components:</b>	Void
<b>Additional information:</b>	For the wording of the listed risk phrases refer to section 16.

**SECTION 4: First aid measures**
**4.1 Description of first aid measures**

<b>General information:</b>	Take affected persons out into the fresh air. Immediately remove any clothing soiled by the product.
<b>After inhalation:</b>	Supply fresh air; consult doctor in case of complaints.
<b>After skin contact:</b>	Immediately wash with water and soap and rinse thoroughly. If skin irritation continues, consult a doctor.
<b>After eye contact:</b>	Rinse opened eye for several minutes under running water. Then consult a doctor.
<b>After swallowing:</b>	If swallowed, seek medical advice immediately and show this container or label.

**4.2 Most important symptoms and effects, both acute and delayed**

Disziness  
Headache

**4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

(Contd. on page 3)

**Safety data sheet**  
 according to 1907/2006/EC, Article 31

Printing date 19.03.2015

Version number 3

Revision: 19.03.2015

**Trade name: Osmo Polyx®-Oil 2K Pure, component A**

(Contd. of page 2)

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

**Suitable extinguishing agents:** CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

**For safety reasons unsuitable extinguishing agents:**

Water with full jet

#### 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

#### 5.3 Advice for firefighters

**Protective equipment:**

Mouth respiratory protective device.

**Additional information**

Cool endangered receptacles with water spray.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

#### 6.2 Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

#### 6.3 Methods and material for containment and cleaning up:

Warm water and cleansing agent

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders).

#### 6.4 Reference to other sections

See Section 13 for disposal information.

No dangerous substances are released.

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

Use only in well ventilated areas.

Keep receptacles tightly sealed.

Keep away from heat and direct sunlight.

Prevent formation of aerosols.

**Information about fire - and explosion protection:**

No special measures required.

#### 7.2 Conditions for safe storage, including any incompatibilities

**Storage:**

**Requirements to be met by storerooms and receptacles:**

Store only in the original receptacle.

Store in a cool location.

**Information about storage in one common storage facility:**

Do not store together with alkalis (caustic solutions).

(Contd. on page 4)

**Safety data sheet**  
 according to 1907/2006/EC, Article 31

Printing date 19.03.2015

Version number 3

Revision: 19.03.2015

**Trade name: Osmo Polyx®-Oil 2K Pure, component A**

(Contd. of page 3)

**Further information about storage conditions:**

Do not store together with oxidising and acidic materials.

None.

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

**7.3 Specific end use(s)**

No further relevant information available.

**SECTION 8: Exposure controls/personal protection**

**Additional information about design of technical facilities:**

No further data; see item 7.

**8.1 Control parameters**

**Ingredients with limit values that require monitoring at the workplace:**

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

**Additional information:**

The lists valid during the making were used as basis.

**8.2 Exposure controls**

**Personal protective equipment: General protective and hygienic measures:**

Do not eat, drink, smoke or sniff while working.

Do not carry product impregnated cleaning cloths in trouser pockets.

Avoid contact with the eyes and skin.

**Respiratory protection:**

Not necessary if room is well-ventilated.

Use suitable respiratory protective device only when aerosol or mist is formed.

**Protection of hands:**

To avoid skin problems reduce the wearing of gloves to the required minimum.

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

**Material of gloves**

Nitrile rubber, NBR

**Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

**For the permanent contact gloves made of the following materials are suitable:**

Nitrile rubber, NBR

**For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:**

Nitrile rubber, NBR

**As protection from splashes gloves made of the following materials are suitable:**

Nitrile rubber, NBR

(Contd. on page 5)

**Safety data sheet**  
 according to 1907/2006/EC, Article 31

Printing date 19.03.2015

Version number 3

Revision: 19.03.2015

**Trade name: Osmo Polyx®-Oil 2K Pure, component A**

(Contd. of page 4)

**Eye protection:** Goggles recommended during refilling  
**Body protection:** Protective work clothing

**SECTION 9: Physical and chemical properties**

**9.1 Information on basic physical and chemical properties**

**General Information**

**Appearance:**

**Form:** Viscous  
**Colour:** Yellowish  
**Odour:** Mild

**Change in condition**

**Melting point/Melting range:** Undetermined.  
**Boiling point/Boiling range:** not applicable

**Flash point:** >100 °C (DIN 53213)

**Self-igniting:** Product is not selfigniting.

**Danger of explosion:** Product does not present an explosion hazard.

**Density at 20 °C:** 0.95-1.00 g/cm<sup>3</sup> (DIN 51757)

**Solubility in / Miscibility with water:**

Not miscible or difficult to mix.

**Viscosity:**

**Kinematic at 20 °C:** 20-35 s s (DIN 53211/4mm)

**Solvent content:**

**VOC (EC)** < 50 g/l (VOC-max. = 500g/l (2010 A/j))

**9.2 Other information** No further relevant information available.

**SECTION 10: Stability and reactivity**

**10.1 Reactivity**

**10.2 Chemical stability**

**Thermal decomposition / conditions to be avoided:**

No decomposition if used according to specifications.

**10.3 Possibility of hazardous reactions**

Reacts with fabric soaked in the product (e.g. cleaning wool).

**10.4 Conditions to avoid**

No further relevant information available.

**10.5 Incompatible materials:**

No further relevant information available.

**10.6 Hazardous decomposition products:**

Carbon monoxide and carbon dioxide  
 Nitrogen oxides (NOx)

(Contd. on page 6)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 19.03.2015

Version number 3

Revision: 19.03.2015

**Trade name: Osmo Polyx®-Oil 2K Pure, component A**

(Contd. of page 5)

**Additional information:****Warning:**

Wash out any used cloth impregnated with this product immediately after use or store in an airtight container (danger of self-ignition)

### SECTION 11: Toxicological information

**11.1 Information on toxicological effects****Acute toxicity:****LD/LC50 values relevant for classification:****96-29-7 2-butanonoxime**

Oral	LD50	3700 mg/kg (rat)
Dermal	LD50	200-2000 mg/kg (rat)
Inhalative	LC50 / 4h	>10.5 mg/l (rat)

**Primary irritant effect:****on the skin:**

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.

**on the eye:**

No irritating effect.

**Sensitisation:**

Sensitising effect by skin contact is possible by prolonged exposure.

**Additional toxicological information:**

The product is not subject to classification according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version. When used and handled according to specifications, the product does not have any harmful effects to our experience and the information provided to us.

**Sensitisation**

Contains 2-butanonoxime. May produce an allergic reaction.

### SECTION 12: Ecological information

**12.1 Toxicity****Aquatic toxicity:****96-29-7 2-butanonoxime**

EC50 / 48h	201 mg/l (daphnia)
IC50 / 72h	11.8 mg/l (algae)
LC50 / 96h	>100 mg/l (fish)

**12.2 Persistence and degradability** No further relevant information available.

**12.3 Bioaccumulative potential** No further relevant information available.

**12.4 Mobility in soil** No further relevant information available.

**Additional ecological information:****General notes:**

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow product to reach ground water, water course or sewage system.

(Contd. on page 7)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 19.03.2015

Version number 3

Revision: 19.03.2015

**Trade name: Osmo Polyx®-Oil 2K Pure, component A**

(Contd. of page 6)

**12.5 Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.**12.6 Other adverse effects** No further relevant information available.**SECTION 13: Disposal considerations****13.1 Waste treatment methods**

**Recommendation** Must not be disposed together with household garbage. Do not allow product to reach sewage system.

**European waste catalogue**

08 01 11	waste paint and varnish containing organic solvents or other dangerous substances
15 01 10	packaging containing residues of or contaminated by dangerous substances

**Uncleaned packaging:**

**Recommendation:** Disposal must be made according to official regulations.

**SECTION 14: Transport information****14.1 UN-Number****ADR, ADN, IMDG, IATA** Void**14.2 UN proper shipping name****ADR, ADN, IMDG, IATA** Void**14.3 Transport hazard class(es)****ADR, ADN, IMDG, IATA****Class** Void**14.4 Packing group****ADR, IMDG, IATA** Void**14.5 Environmental hazards:****Marine pollutant:** No**14.6 Special precautions for user** Not applicable.**14.7 Transport in bulk according to Annex II of****MARPOL73/78 and the IBC Code** Not applicable.**UN "Model Regulation":**

-

(Contd. on page 8)

**Safety data sheet**  
 according to 1907/2006/EC, Article 31

Printing date 19.03.2015

Version number 3

Revision: 19.03.2015

**Trade name: Osmo Polyx®-Oil 2K Pure, component A**

(Contd. of page 7)

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

##### National regulations:

**VOC (EC)** < 50 g/l (VOC-max. = 500 g/l (2010 A/i))

**15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

**Department issuing MSDS:** product safety department

**Contact:** Hr. Dr. Starp

**Abbreviations and acronyms:** ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
 IMDG: International Maritime Code for Dangerous Goods  
 IATA: International Air Transport Association  
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals  
 EINECS: European Inventory of Existing Commercial Chemical Substances  
 ELINCS: European List of Notified Chemical Substances  
 CAS: Chemical Abstracts Service (division of the American Chemical Society)  
 VOC: Volatile Organic Compounds (USA, EU)  
 LC50: Lethal concentration, 50 percent  
 LD50: Lethal dose, 50 percent

**\* Data compared to the previous version altered.**



**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 21.02.2013

Version number 3

Revision: 21.02.2013

### 1 Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

**Trade name:** Hardener for Osmo Polyx®-Oil 2K Pure, Component B

**Article number:** 6125/B

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use : Hardener for coating materials or adhesives for industrial and trade applications  
Uses advised against : Not suitable for use in homemaker (DIY) applications.

#### Application of the substance / the preparation

Hardening agent/ Curing agent

#### 1.3 Details of the supplier of the safety data sheet

**Manufacturer/Supplier:** Osmo Holz und Color GmbH & Co. KG  
Affhüppen Esch 12  
D-48231 Warendorf

#### Further information obtainable from:

Product safety department  
Phone: +49 (0) 251 / 692 - 188  
Fax: +49 (0) 251 / 692 - 462  
e-mail: helmut.starp@osmo.de

#### 1.4 Emergency telephone number:

emergency phone no. Berlin (24h): +49 (0) 30 / 30686 790 advisory service in German and English

### 2 Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification according to Regulation (EC) No 1272/2008

Acute Tox. 4 H332 Harmful if inhaled.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

##### Classification according to Directive 67/548/EEC or Directive 1999/45/EC

Xn; Harmful

R20: Harmful by inhalation.

Xi; Irritant

R37: Irritating to respiratory system.

Xi; Sensitising

R43: May cause sensitisation by skin contact.

#### 2.2 Label elements

##### Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 21.02.2013

Version number 3

Revision: 21.02.2013

**Trade name: Hardener for Osmo Polyx®-Oil 2K Pure, Component B**

(Contd. of page 1)

**Hazard pictograms**

GHS07

**Signal word**

Warning

**Hazard-determining components of labelling:**Hexamethylen-1,6-diisocyanat homopolymer  
hexamethylene-di-isocyanate**Hazard statements**H332 Harmful if inhaled.  
H317 May cause an allergic skin reaction.  
H335 May cause respiratory irritation.  
Contains isocyanates. May produce an allergic reaction.**Precautionary statements**P101 If medical advice is needed, have product container or label at hand.  
P102 Keep out of reach of children.  
P103 Read label before use.  
P260 Do not breathe dust/fume/gas/mist/vapours/spray.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P302+P352 IF ON SKIN: Wash with plenty of soap and water.  
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.  
P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.**2.3 Other hazards****Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.

### 3 Composition/information on ingredients

**3.2 Chemical characterization: Mixtures****Description:** Substance  
aliphatic polyisocyanate**Dangerous components:**

CAS: 28182-81-2 NLP: 500-060-2	Hexamethylen-1,6-diisocyanat homopolymer Xn R20;  Xi R37;  Xi R43 Acute Tox. 4, H332; Skin Sens. 1, H317; STOT SE 3, H335	50-100%
CAS: 822-06-0 EINECS: 212-485-8 Index number: 615-011-00-1	hexamethylene-di-isocyanate T R23;  Xn R42/43;  Xi R36/37/38 Acute Tox. 3, H331 Resp. Sens. 1, H334 Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	≤1%

(Contd. on page 3)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 21.02.2013

Version number 3

Revision: 21.02.2013

**Trade name: Hardener for Osmo Polyx®-Oil 2K Pure, Component B**

**Additional information:**

For the wording of the listed risk phrases refer to section 16.

(Contd. of page 2)

#### 4 First aid measures

##### 4.1 Description of first aid measures

**General information:**

Immediately remove any clothing soiled by the product.

**After inhalation:**

Supply fresh air; consult doctor in case of complaints.

**After skin contact:**

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

**After eye contact:**

Rinse opened eye for several minutes under running water. Then consult a doctor.

**After swallowing:**

Do not induce vomiting; call for medical help immediately.

##### 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

##### 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

#### 5 Firefighting measures

##### 5.1 Extinguishing media

**Suitable extinguishing agents:**
CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray.
**For safety reasons unsuitable extinguishing agents:**

Water with full jet

##### 5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

Carbon monoxide (CO)

Nitrogen oxides (NO<sub>x</sub>)

(Traces)

Hydrogen cyanide (HCN)

##### 5.3 Advice for firefighters

**Protective equipment:**

Do not inhale explosion gases or combustion gases.

Wear self-contained respiratory protective device.

Wear fully protective suit.

**Additional information**

Collect contaminated fire fighting water separately. It must not enter the sewage system.

#### 6 Accidental release measures

##### 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

##### 6.2 Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

(Contd. on page 4)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 21.02.2013

Version number 3

Revision: 21.02.2013

**Trade name: Hardener for Osmo Polyx®-Oil 2K Pure, Component B**

(Contd. of page 3)

**6.3 Methods and material for containment and cleaning up:**

Pick up mechanically.  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders).  
Dispose of the material collected according to regulations.

**6.4 Reference to other sections**

See Section 13 for disposal information.

**7 Handling and storage**

**7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.

**Information about fire - and explosion protection:**

Fumes can combine with air to form an explosive mixture.

**7.2 Conditions for safe storage, including any incompatibilities**

**Storage:**

**Requirements to be met by storerooms and receptacles:**

Store in a cool location.  
Prevent any seepage into the ground.  
Store only in the original receptacle.

**Information about storage in one common storage facility:**

Store away from foodstuffs.

**Further information about storage conditions:**

Store receptacle in a well ventilated area.  
Store in cool, dry conditions in well sealed receptacles.

**7.3 Specific end use(s)**

No further relevant information available.

**8 Exposure controls/personal protection**

**Additional information about design of technical facilities:**

No further data; see item 7.

**8.1 Control parameters**

**Ingredients with limit values that require monitoring at the workplace:**

**822-06-0 hexamethylene-di-isocyanate**

WEL	Long-term value: 0.1 mg/m <sup>3</sup> as Co; Carc
-----	---

**Additional information:**

The lists valid during the making were used as basis.

**8.2 Exposure controls**

**Personal protective equipment:**

**General protective and hygienic measures:**

Wash hands before breaks and at the end of work.  
Immediately remove all soiled and contaminated clothing  
Keep away from foodstuffs, beverages and feed.

(Contd. on page 5)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 21.02.2013

Version number 3

Revision: 21.02.2013

**Trade name: Hardener for Osmo Polyx®-Oil 2K Pure, Component B**

(Contd. of page 4)

<b>Respiratory protection:</b>	Avoid contact with the eyes and skin. Do not eat, drink, smoke or sniff while working. In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device. Filter A/P2 In case of hypersensitivity of the respiratory tract and skin (e.g. asthmatics and those who suffer from chronic bronchitis and chronic skin complaint) it is inadvisable to work with the product.
<b>Protection of hands:</b>	Protective gloves The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
<b>Material of gloves</b>	The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. Butyl rubber, BR Fluorocarbon rubber (Viton)
<b>Penetration time of glove material</b>	The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
<b>For the permanent contact gloves made of the following materials are suitable:</b>	chemical resistant gloves (EN 374) Butyl rubber, BR
<b>Not suitable are gloves made of the following materials:</b>	Nitrile rubber, NBR
<b>Eye protection:</b>	Safety glasses Face protection
<b>Body protection:</b>	Use protective suit. Protective work clothing

## 9 Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### General Information

##### Appearance:

<b>Form:</b>	Fluid
<b>Colour:</b>	Colourless
<b>Odour:</b>	Light
<b>Odour threshold:</b>	Not determined.

**pH-value:** Not applicable

(Contd. on page 6)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 21.02.2013

Version number 3

Revision: 21.02.2013

**Trade name: Hardener for Osmo Polyx®-Oil 2K Pure, Component B**

(Contd. of page 5)

<b>Change in condition</b>	
<b>Melting point/Melting range:</b>	Undetermined.
<b>Boiling point/Boiling range:</b>	285 °C (bei 1013 hPa DIN 53171)
<b>Flash point:</b>	> 100 °C (DIN EN 22719)
<b>Flammability (solid, gaseous):</b>	Not applicable.
<b>Ignition temperature:</b>	ca 435 °C (DIN 51794)
<b>Decomposition temperature:</b>	ca. 150 °C
<b>Self-igniting:</b>	Product is not selfigniting.
<b>Danger of explosion:</b>	Product does not present an explosion hazard.
<b>Vapour pressure at 20 °C:</b>	< 0.00001 hPa (EG A4)
<b>Density at 20 °C:</b>	1.15 g/cm <sup>3</sup> (DIN 51757)
<b>Relative density</b>	Not determined.
<b>Solubility in / Miscibility with water:</b>	Not miscible or difficult to mix.
<b>Partition coefficient (n-octanol/water):</b> 8.38 log POW	
<b>Viscosity:</b>	
<b>Dynamic:</b>	Not determined.
<b>Kinematic at 20 °C:</b>	40 s (DIN 53211/6mm)
<b>9.2 Other information</b>	No further relevant information available.

## 10 Stability and reactivity

### 10.1 Reactivity

### 10.2 Chemical stability

#### Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

### 10.3 Possibility of hazardous reactions

Reacts with alcohols.

Reacts with amines.

Decomposes with water, acids and alkalis.

Danger of bursting.

### 10.4 Conditions to avoid

No further relevant information available.

### 10.5 Incompatible materials:

No further relevant information available.

### 10.6 Hazardous decomposition products:

No hazardous decomposition products when stored and handled correctly.

(Contd. on page 7)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 21.02.2013

Version number 3

Revision: 21.02.2013

**Trade name: Hardener for Osmo Polyx®-Oil 2K Pure, Component B**

(Contd. of page 6)

Keine gefährlichen Zersetzungsprodukte bei sachgemäßer Lagerung und Handhabung.

### 11 Toxicological information

#### 11.1 Information on toxicological effects

##### Acute toxicity:

##### LD/LC50 values relevant for classification:

#### 28182-81-2 Hexamethylen-1,6-diisocyanat homopolymer

Oral	LD50	>5000 mg/kg (rat)
Inhalative	LC50 / 4h	543 mg/l (rat) (OECD 403)

#### 822-06-0 hexamethylene-di-isocyanate

Oral	LD50	738 mg/kg (rat)
Dermal	LD50	593 mg/kg (rat)

##### Primary irritant effect:

**on the skin:** At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.

#### 28182-81-2 Hexamethylen-1,6-diisocyanat homopolymer

Dermal	.	litt irriterende (rabbit) (OECD 404)
--------	---	--------------------------------------

**on the eye:** Irritating effect.

**Sensitization:** Sensitization possible through skin contact.

#### 28182-81-2 Hexamethylen-1,6-diisocyanat homopolymer

Inhalative	.	positiv (mouse) (Lokaler Lymphknoten-Test (LLNA))
------------	---	---

##### Other information (about experimental toxicology):

Animal tests and other research indicate that skin contact with diisocyanates can play a role in causing isocyanate sensitization and respiratory reaction.

##### Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

Harmful

Special properties/effects: Over-exposure, especially when spraying coatings containing isocyanate without the necessary precautions, entails the risk of concentration-dependent irritating effects on eyes, nose throat, and respiratory tract. Delayed appearance of the complaints and development of hypersensitivity (difficult breathing, coughing, asthma) are possible. Hypersensitive persons may suffer from these effects even at low isocyanate concentrations, including concentrations below the UK Workplace Exposure Limit (WEL). Prolonged contact with the skin may cause tanning and irritant effects.

(Contd. on page 8)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 21.02.2013

Version number 3

Revision: 21.02.2013

**Trade name: Hardener for Osmo Polyx®-Oil 2K Pure, Component B**

(Contd. of page 7)

**CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)**

Genotoxicity in vitro:  
hexamethylen-1,6-diisocyanat homopolymer  
Test type: Ames test; Result: negative; Method: OECD Test Guideline 471

Test type: Chromosome aberration test in vitro  
Result: negative; Method: OECD Test Guideline 473  
Toxicological studies of a comparable product.

Test type: Point mutation in mammalian cells (HPRT test)  
Result: negative; Method: OECD Test Guideline 476  
Toxicological studies of a comparable product.

## 12 Ecological information

### 12.1 Toxicity

**Aquatic toxicity:**

**28182-81-2 Hexamethylen-1,6-diisocyanat homopolymer**

EC50 / 48h	> 100 mg/l (daphnia) (OECD 202)
IC50 / 72h	199 mg/l (algae) (OECD 201)
LC50 / 96h	> 100 mg/l (Brachydanio rerio) (OECD 203)

**12.2 Persistence and degradability** Not easily biodegradable

### 12.3 Bioaccumulative potential

**28182-81-2 Hexamethylen-1,6-diisocyanat homopolymer**

log POW	ca 8.38 (-)
---------	-------------

### 12.4 Mobility in soil

Surface tension: ca. 46.5 mN/m at 20 °C  
Oberflächenspannung: ca. 46,5 mN/m bei 20 °C

**Ecotoxicological effects:**

**Behaviour in sewage processing plants:**

**28182-81-2 Hexamethylen-1,6-diisocyanat homopolymer**

EC0 / 3h	>100 mg/l (daphnia)
EC50	> 10.000 mg/l (activated sludge organism) (OECD Guideline for Testing of Chemicals, No.209)

**Additional ecological information:**

**General notes:**

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

The resin reacts with water at the interface forming CO<sub>2</sub> and a solid insoluble product with high melting point (polyurea). This reaction is accelerated by surfactants (e.g. detergents) or by watersoluble solvents. Previous experience shows that polyurea is inert and non-degradable.

(Contd. on page 9)



**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 21.02.2013

Version number 3

Revision: 21.02.2013

**Trade name: Hardener for Osmo Polyx®-Oil 2K Pure, Component B**

(Contd. of page 8)

**12.5 Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.**12.6 Other adverse effects** No further relevant information available.**13 Disposal considerations****13.1 Waste treatment methods****Recommendation** Must not be disposed together with household garbage. Do not allow product to reach sewage system.**Uncleaned packaging:**

**Recommendation:** Disposal must be made according to official regulations.

Waste treatment methods

After final product withdrawal, all residues must be removed from containers (drip-free, powderfree or paste-free). Once the product residues adhering to the walls of the containers have been rendered harmless, the product and hazard labels must be invalidated. These containers can be returned for recycling to the appropriate centres set up within the framework of the existing takeback scheme of the chemical industry. Containers must be recycled in compliance with national legislation and environmental regulations.

**14 Transport information****14.1 UN-Number****ADR, ADN, IMDG, IATA** Void**14.2 UN proper shipping name****ADR, ADN, IMDG, IATA** Void**14.3 Transport hazard class(es)****ADR, ADN, IMDG, IATA****Class** Void**14.4 Packing group****ADR, IMDG, IATA** Void**14.5 Environmental hazards:****Marine pollutant:** No**14.6 Special precautions for user**

Not applicable.

**14.7 Transport in bulk according to Annex II of****MARPOL73/78 and the IBC Code** Not applicable.**Transport/Additional information:**

Not dangerous according to the above specifications.

Special precautions for user : Not dangerous cargo.

(Contd. on page 10)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 21.02.2013

Version number 3

Revision: 21.02.2013

**Trade name: Hardener for Osmo Polyx®-Oil 2K Pure, Component B**

(Contd. of page 9)

Slight smell. Keep dry.  
Avoid heat above +50 °C.  
Keep away from foodstuffs, acids and alkalis.

UN "Model Regulation":

-

### 15 Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

##### National regulations:

##### Other regulations, limitations and prohibitive regulations

Other regulations: The European Committee of Paint, Printing Ink and Artists' Colours Manufacturers' Associations (CEPE) provides the following information on coatings containing isocyanates: Ready-to-use paints containing isocyanates may have an irritant effect on mucous membranes - especially on breathing organs - and cause hypersensitivity reactions. Inhalation of vapor or spray mist may cause sensitisation. When handling paints containing isocyanates all precautions required for solvent-containing paints must be followed. Vapor and spray mist in particular should not be inhaled. Allergics and asthmatics as well as people prone to respiratory ailments should not work with isocyanate containing paints.

**15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

##### Relevant phrases

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
.....	
R20	Harmful by inhalation.
R23	Toxic by inhalation.
R36/37/38	Irritating to eyes, respiratory system and skin.
R37	Irritating to respiratory system.
R42/43	May cause sensitisation by inhalation and skin contact.
R43	May cause sensitisation by skin contact.

**Department issuing MSDS:** product safety department

**Contact:** Hr. Dr. Starp

(Contd. on page 11)

***Safety data sheet***  
***according to 1907/2006/EC, Article 31***

Printing date 21.02.2013

Version number 3

Revision: 21.02.2013

**Trade name: Hardener for Osmo Polyx®-Oil 2K Pure, Component B**

(Contd. of page 10)

**Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organization

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

**\* Data compared to the previous  
version altered.**

GB