

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 28.03.2012

Version number 3

Revision: 28.03.2012

## 1 Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Trade name:** Osmo Wood Wax Finish Creativ

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Application of the substance / the preparation**

Coating compound/ Surface coating/ paint

### 1.3 Details of the supplier of the safety data sheet

**Manufacturer/Supplier:** Osmo Holz und Color GmbH & Co. KG  
Affhüppen Esch 12  
D-48231 Warendorf

**Further information obtainable from:**

Product safety department  
Phone: +49 (0) 251 / 692 - 188  
Fax: +49 (0) 251 / 692 - 462  
e-mail: helmut.starp@osmo.de

**1.4 Emergency telephone number:**

emergency phone no. Berlin (24h): +49 (0) 30 / 30686 790 advisory service in German and English

## 2 Hazards identification

### 2.1 Classification of the substance or mixture

**Classification according to Directive 67/548/EEC or Directive 1999/45/EC**

Not applicable.

**Information concerning particular hazards for human and environment:**

The product does not have to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

**Classification system:**

The classification is according to the latest editions of the EU-lists and extended by company and literature data.

### 2.2 Label elements

**Labelling according to EU guidelines:**

Although this product is not subject to identification regulations, we recommend that the safety suggestions are observed.

**Safety phrases:**

- 2 Keep out of the reach of children.
- 24/25 Avoid contact with skin and eyes.
- 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- 46 If swallowed, seek medical advice immediately and show this container or label.
- 51 Use only in well-ventilated areas.

(Contd. on page 2)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 28.03.2012

Version number 3

Revision: 28.03.2012

**Trade name: Osmo Wood Wax Finish Creativ**

(Contd. of page 1)

**Special labelling of certain preparations:**

**Warning:**

Wash out any used cloth impregnated with this product immediately after use or store in an airtight container (danger of self-ignition)

Contains 2-butanonoxime. May produce an allergic reaction.

Safety data sheet available for professional user on request.

**Additional information:**

Observe the general safety regulations when handling chemicals.

Always wear a dust mask when sanding.

**2.3 Other hazards**

**Results of PBT and vPvB assessment**

**PBT:** Not applicable.

**vPvB:** Not applicable.

### 3 Composition/information on ingredients

**3.2 Chemical characterization: Mixtures**

**Description:** Mixture of substances listed below with nonhazardous additions.

**Dangerous components:**

CAS: 64742-48-9	aliphatic hydrocarbons, C10-C13	25-50%
EC number: 918-481-9	Xn R65	
Index number: 649-327-00-6	R66	
Reg.nr.: 01-2119457273-39	Acute Tox. 3, H331; Asp. Tox. 1, H304	

**Additional information:** For the wording of the listed risk phrases refer to section 16.

### 4 First aid measures

**4.1 Description of first aid measures**

**General information:** Immediately remove any clothing soiled by the product.

**After inhalation:** Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

**After skin contact:** Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

**After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.

**After swallowing:** If swallowed, seek medical advice immediately and show this container or label.

Induce vomiting only, if affected person is fully conscious.

**4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.

(Contd. on page 3)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 28.03.2012

Version number 3

Revision: 28.03.2012

**Trade name: Osmo Wood Wax Finish Creativ**

(Contd. of page 2)

**4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

## 5 Firefighting measures

### 5.1 Extinguishing media

**Suitable extinguishing agents:**

CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

**For safety reasons unsuitable extinguishing agents:**

Water with full jet

### 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

### 5.3 Advice for firefighters

**Protective equipment:**

Mouth respiratory protective device.

**Additional information**

Cool endangered receptacles with water spray.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

## 6 Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Keep away from ignition sources.

Ensure adequate ventilation

### 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

### 6.3 Methods and material for containment and cleaning up:

Warm water and cleansing agent

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders).

### 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## 7 Handling and storage

### 7.1 Precautions for safe handling

Keep receptacles tightly sealed.

Keep away from heat and direct sunlight.

Use only in well ventilated areas.

Prevent formation of aerosols.

**Information about fire - and explosion protection:**

Keep ignition sources away - Do not smoke.

(Contd. on page 4)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 28.03.2012

Version number 3

Revision: 28.03.2012

**Trade name: Osmo Wood Wax Finish Creativ**

(Contd. of page 3)

**7.2 Conditions for safe storage, including any incompatibilities****Storage:****Requirements to be met by****storerooms and receptacles:**

Store in a cool location.  
Store only in the original receptacle.

**Information about storage in one common storage facility:**

Do not store together with alkalis (caustic solutions).  
Do not store together with oxidizing and acidic materials.

**Further information about storage conditions:**

Keep container tightly sealed.  
Store receptacle in a well ventilated area.  
Protect from heat and direct sunlight.

**7.3 Specific end use(s)**

No further relevant information available.

**8 Exposure controls/personal protection**

**Additional information about design of technical facilities:**

No further data; see item 7.

**8.1 Control parameters****Ingredients with limit values that require monitoring at the workplace:**

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

**Additional information:**

The lists valid during the making were used as basis.

**8.2 Exposure controls****Personal protective equipment:****General protective and hygienic measures:**

Immediately remove all soiled and contaminated clothing  
Avoid contact with the eyes and skin.  
Do not eat, drink, smoke or sniff while working.  
Do not carry product impregnated cleaning cloths in trouser pockets.

**Respiratory protection:**

Not necessary if room is well-ventilated.  
Use suitable respiratory protective device only when aerosol or mist is formed.  
Short term filter device:

Gas filter EN 14387 Type A (organic gas / vapor (boiling point &gt; 65 ° C)).

**Protection of hands:**

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

**Material of gloves**

Nitrile rubber, NBR

(Contd. on page 5)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 28.03.2012

Version number 3

Revision: 28.03.2012

**Trade name: Osmo Wood Wax Finish Creativ**

(Contd. of page 4)

**Penetration time of glove material** The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

**For the permanent contact gloves made of the following materials are suitable:**

Nitrile rubber, NBR

**As protection from splashes gloves made of the following materials are suitable:**

Nitrile rubber, NBR

**Eye protection:**

Goggles recommended during refilling

**Body protection:**

Protective work clothing

## 9 Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### General Information

##### Appearance:

**Form:** Fluid

**Colour:** According to product specification

**Odour:** Mild

#### Change in condition

**Melting point/Melting range:** Undetermined.

**Boiling point/Boiling range:** > 180°C (DIN 51751)

**Flash point:** ≥ 61 °C (DIN 52231)

**Ignition temperature:** 240°C

**Self-igniting:** Product is not selfigniting.

**Danger of explosion:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

#### Explosion limits:

**Lower:** 0.6 Vol % (Lösemittel)

**Upper:** 7.0 Vol % (Lösemittel)

**Vapour pressure:** 3 hPa [20°C]

**Density at 20°C:** 1.05 - 1.40 g/cm<sup>3</sup> (DIN 51757)

**Solubility in / Miscibility with water:**

Not miscible or difficult to mix.

#### Viscosity:

**Kinematic at 20°C:** >81 s (DIN 53211/4)

**Solvent separation test:** < 3 % (ADR 2.2.1.4f)

(Contd. on page 6)

**Safety data sheet**  
 according to 1907/2006/EC, Article 31

Printing date 28.03.2012

Version number 3

Revision: 28.03.2012

**Trade name: Osmo Wood Wax Finish Creativ**

(Contd. of page 5)

**Solvent content:****VOC (EC)**

&lt; 400 g/l (VOC-max. = 400 g/l (2010 A/e))

**9.2 Other information**

No further relevant information available.

## 10 Stability and reactivity

**10.1 Reactivity****10.2 Chemical stability****Thermal decomposition /****conditions to be avoided:**

No decomposition if used and stored according to specifications.

**10.3 Possibility of hazardous reactions**

Reacts with fabric soaked in the product (e.g. cleaning wool).

**10.4 Conditions to avoid**

No further relevant information available.

**10.5 Incompatible materials:**

No further relevant information available.

**10.6 Hazardous decomposition products:**

Formation of toxic gases is possible during heating or in case of fire.

Nitrogen oxides (NO<sub>x</sub>)

Carbon monoxide and carbon dioxide

**Additional information:**

Warning:

Wash out any used cloth impregnated with this product immediately after use or store in an airtight container (danger of self-ignition)

## 11 Toxicological information

**11.1 Information on toxicological effects****Acute toxicity:****LD/LC50 values relevant for classification:****64742-48-9 aliphatic hydrocarbons, C10-C13**

Oral LD50 &gt; 5000 mg/kg (rat) (OECD 401)

Dermal LD50 &gt; 5000 mg/kg (rat) (OECD 402)

Inhalative LC50 / 4h &gt; 5 mg/l (rat) (OECD 403)

**96-29-7 2-butanonoxime**

Oral LD50 3700 mg/kg (rat)

Dermal LD50 200-2000 mg/kg (rat)

Inhalative LC50 / 4h &gt;10.5 mg/l (rat)

**Primary irritant effect:****on the skin:**

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.

**on the eye:**

Irritating effect.

(Contd. on page 7)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 28.03.2012

Version number 3

Revision: 28.03.2012

**Trade name: Osmo Wood Wax Finish Creativ**

(Contd. of page 6)

**Sensitization:** No sensitizing effects known.

**Additional toxicological information:**

The product is not subject to classification according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version. When used and handled according to specifications, the product does not have any harmful effects to our experience and the information provided to us. Inhalation of concentrated vapours as well as oral intake will lead to anaesthesia-like conditions and headache, dizziness, etc.

**12 Ecological information**

**12.1 Toxicity**

**Aquatic toxicity:**

**64742-48-9 aliphatic hydrocarbons, C10-C13**

Biodegradability	easily degradable (-)
EC50 / 48h	> 1000 mg/l (daphnia) (OECD 202)
EC50/ 72h	> 1000 mg/l (algae) (OECD 201)
LC50 / 96h	> 1000 mg/l (fish) (OECD 203)

**96-29-7 2-butanonoxime**

EC50 / 48h	201 mg/l (daphnia)
IC50 / 72h	11.8 mg/l (algae)

**12.2 Persistence and degradability** No further relevant information available.

**12.3 Bioaccumulative potential** No further relevant information available.

**12.4 Mobility in soil** No further relevant information available.

**Ecotoxicological effects:**

**Behaviour in sewage processing plants:**

**96-29-7 2-butanonoxime**

EC50/ 96h	>100 mg/l (fish)
-----------	------------------

**Additional ecological information:**

**General notes:** Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow product to reach ground water, water course or sewage system.

**12.5 Results of PBT and vPvB assessment**

**PBT:** Not applicable.

**vPvB:** Not applicable.

**12.6 Other adverse effects** No further relevant information available.

(Contd. on page 8)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 28.03.2012

Version number 3

Revision: 28.03.2012

**Trade name: Osmo Wood Wax Finish Creativ**

(Contd. of page 7)

### 13 Disposal considerations

#### 13.1 Waste treatment methods

**Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

#### European waste catalogue

08 01 11	waste paint and varnish containing organic solvents or other dangerous substances
15 01 10	packaging containing residues of or contaminated by dangerous substances

#### Uncleaned packaging:

**Recommendation:**

Disposal must be made according to official regulations.

### 14 Transport information

#### 14.1 UN-Number

ADR, ADN, IMDG, IATA

Void

#### 14.2 UN proper shipping name

ADR, ADN, IMDG, IATA

Void

#### 14.3 Transport hazard class(es)

ADR, ADN, IMDG, IATA

Class

Void

#### 14.4 Packing group

ADR, IMDG, IATA

Void

#### 14.5 Environmental hazards:

Marine pollutant:

No

#### 14.6 Special precautions for user

Not applicable.

#### 14.7 Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code

Not applicable.

### 15 Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

##### National regulations:

VOC (EC)

< 400 g/l (VOC-max. = 400 g/l (2010 A/e))

**15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

(Contd. on page 9)



**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 28.03.2012

Version number 3

Revision: 28.03.2012

**Trade name: Osmo Wood Wax Finish Creativ**

(Contd. of page 8)

**16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

**Relevant phrases**

H304 May be fatal if swallowed and enters airways.

H331 Toxic if inhaled.

R65 Harmful: may cause lung damage if swallowed.

R66 Repeated exposure may cause skin dryness or cracking.

**Department issuing MSDS:**

product safety department

**Contact:**

Hr. Dr. Starp

**\* Data compared to the previous  
version altered.**